



## CARE, MAINTENANCE AND SAFETY INSTRUCTIONS

### FOR COMPOSITE CO-EXTRUSION SHEDS

- The shed is generally used for storing objects. The shed is not especially designed for residential purposes.
- Check the shed regularly for stability and make sure that the location is level.
- Be careful when handling parts with steel edges.
- For the construction and handling of the shed, please only use tools that are listed in the assembly instructions.
- Avoid using lawnmowers and mechanical scythe in the immediate vicinity of the shed.
- To clean the shed, start by rinsing it with a garden hose to remove surface debris. Then you can use a soft-bristled brush with warm soapy water. Use pressure washers with extreme caution, using only pressures less than 3,000 psi with a wide tip, and maintaining a distance of at least 10 inches (25cm) from the cladding surface.
- Do not damage, gouge, scrape or puncture any surface of the shed, using metal shovels or sharp-edge tools to remove snow and ice on any surface of the garden shed or in any other way. Instead, use a plastic shovel and recommended calcium chloride or rock salt to melt snow and ice.
- Do not paint, stain or apply other coating materials or any other chemical substances, including detergents or pesticides to the shed.
- Clean oil or grease spills as soon as possible and at the latest within seven days. Start by rinsing with a garden hose and use warm soapy water and a soft-bristled brush. If that's not enough, you can use recommended all-purpose cleaners, including for composite, and follow the manufacturer's instructions carefully.
- Do not store any hot objects in the shed, such as recently used grills or blowtorches, or any volatile chemicals.

- Do not lean heavy objects against the walls of the shed, as it could deform the entire structure.
- Keep the roof free of snow and accumulated foliage. Large amounts of snow can damage the shed and make it dangerous for entering.
- Ensure there is adequate ventilation in the shed to prevent excess moisture.
- Always keep the doors closed and locked when the composite shed is not in use to avoid any kind of wind damage.
- If there is mold present, you can use a garden hose and warm soapy water with a soft-bristled brush. If that's not enough, you can use recommended cleaners, including for mold, and follow the manufacturer's instructions carefully.
- Avoid direct water projection from an automatic watering system onto the composite boards or other parts of the shed, as this water could cause permanent stains where it hits the surface.
- Most construction chinks are designed to withstand cleaning. To avoid any difficulties, it is recommended to test chalk for ease of removal before using it. If chalk lines or stains persist even after attempting to remove them, it is best to contact the chalk manufacturer for specific cleaning instructions.